



Advanced cash automation with industry-leading capacity and multi-currency options.

Use the power of innovative cash recycling with the new high-capacity **LTA-450**; a teller-friendly solution that delivers optimal efficiency, convenience and security – all while allowing you to build better relationships with your customers. The **LTA-450** can elevate service levels and increase profitability at the same time. And its breakthrough capacity will accommodate even the busiest of branches.

CAPACITY/EFFICIENCY

- Higher capacity cassettes — up to 3800 notes
- Up to 22,800 note deposited
- True split cassette capability allowing for up to 12 recycling cassettes
- Upgraded electronics boards for expedited transactions
- Continuous feed for efficient transactions
- Automatic, unattended self-audit

SECURITY

- Serial number recognition and tracking
- Counterfeit/damaged note validation/return
- Operational cassettes accessible with tamper switch and lock and key
- Transit cassette accessible with safe exposure
- Reduced cash access and floor risk due to minimal transfers

CONVENIENCE/FLEXIBILITY

- Continuous deposit/withdraw capabilities
- Various cassette options (high capacity, split cassette, mixed denominations)
- Up to 128 denominations supported and 12 recycled
- 8" tilting touch screen for teller, multi-teller or customer use
- Note jam autorecovery
- Supports multiple currencies

AFFORDABILITY

With flexible integration options and unmatched support and service, the LTA-450 makes high-capacity cash recycling a cost-effective solution for your bank or credit union.





Multiple Cassette Options



The LTA-450 Increases Efficiency, Reduces Cost and Maximizes Cash Security for Your Busiest Branches

FEATURES

- Up to 12 recycling cassettes
- Flexible cassette configurations to meet branch requirements
- Up to 3,800 notes per recycling and operational cassette
- Up to 1,500 notes per multi-denomination recycling cassette
- Input hopper capacity: Max. 600 notes
- Output hopper capacity: Max. 300 notes
- Accepts 128 different denominations
- Recycling of up to 12 denominations

SYSTEM PLATFORM

- Windows 10 IOT ENTERPRISE

CUSTOMER INTERFACE

- 8" wide LCD with touch screen

COMMUNICATION

- TCP/IP

SAFE

- UL 291

LOCK

- LaGard 39e, Other optional electronic locks available

ALARM

- Prepared for alarm integration, Door, Seismic/Thermal, Duress/Silent

OPTIONS

- Safe Lock options
- Alarm

SPEED

- 12 notes per second

POWER CONSUMPTION

- Standby: 70W
- Operation: 560W

NOISE EMISSION

- Standby: 46dBA
- Operation: 70dBA

POWER SUPPLY

- AC 100-240V, 50-60Hz

DIMENSIONS (HxWxD)

- UL 291: 31" x 15" x 44"
(793 x 375 x 1,116 mm)

WEIGHT

- UL 291: 1058 lbs (480kg)

ENVIRONMENTAL CONDITIONS

- Operation: +41°F to +104°F (+5°C to +40°C), 25% to 85% relative humidity
- Transport and storage: +14°F to 122°F (-10°C to +50°C), 10% to 90% relative humidity

See the LTA-450 difference for yourself.