NCR SelfServ[™] 84 Drive-up

Exterior through-the-wall Multi-Function ATM & ITM

Key values

Transform

NCR Interactive Assisted Teller enabled. Connect consumers to the efficient delivery of convenient live teller services from their vehicle across flexible hours and locations.

Attract

Infinity Display: supports multi-touch. 15" or 19" LCD screen. Integrated customized branding opportunities for financial institutions.

Engage

Supports NCR Enterprise SW platform—includes personalization and targeted marketing opportunities. Enable the digital first experience. Engage mobile first consumers.

Available

Enhanced ATM module reliability via Media Handling 2.0. Flexible, future-proofed dispense, deposit and recycling options. Performance enhanced durable design.

Manage

Service intervention process improvements. Full range of common parts across all solutions. Improved device level intelligence.

Secure

Security designed in for more effective risk management and fraud prevention. Includes: strengthened shutter, cash/consumer camera and new flush SPS card reader.



It's not just what it does. It's what it does for you.





Technical specifications

Product dimensions

rouace annensions			
•	HEIGHT	59.57"	(1,513mm)*
•	WIDTH	30.31″	(770mm)*
٠	DEPTH		
	Long sleeve	49.13"	(1,248mm)
	Short sleeve	44.65"	(1,134mm)
٠	WEIGHT**		
	CEN I	1,884lbs	(855kg)

Consumer interface

- Infinity Display Supports multi-touch. 15" or 19" brightened color LCD screen
- Media Entry/Exit Indicators Dynamic active customizable color LEDs. Directional and pulsing user guidance MEEIs
- Lighting Task Lighting. Ambient light sensing
- PIN Pad Recessed Encrypting (Polycarbonate or stainless steel)
- Card Reader EMV Ready (Dip, Motorized IMCRW)
- Contactless Integrated Reader (via card, smartphone or smartwatch)
- Audio Public/Private. Enhanced speakers. Noise reducing microphone

Media handling 2.0 technology

- Dispense S2 Media Dispense Module: up to 60 note bunch, 2,500 notes per cassette. Up to 25,000 note capacity (5 high)****. Vacuum based with adaptive media picking technology
- Deposit SDM2: up to 100 mixed media bunch cash + check in a single transaction.
 Store up to 4,000 notes + 400 checks.
 4-way bundle orientation. Two storage variants
- Recycle/Deposit GBxx2: up to 200 notes per transaction. Store up to 2,300 notes per cassette (deposit). Up to 2,000 notes (recycle). Enhanced note pre-acceptor and separator

Printers

 Thermal Receipt/Journal Printer, options – Dual roll and 2ST

Security

- Supports "Picture in Picture" security
- Privacy filter enabled display
- Cameras 3rd party consumer camera and optional cash slot camera enable
- SolidCore Software Suite
- Integrated Skimming Protection Solution (SPS)
- UL437 Topbox lock
- Safes CEN I, CEN III, CEN III GasEx, CEN IV, CEN IV GasEx options. Safe Heater with S2

Environmental

- Standard: -31°F to 122°F (-35°C to 50°C)
- Humidity :10% to 100%
- Acoustics 65dB (A) idle 68dB operating. Max 75dB (A) fan
- Severe environment protection kit

Servicing

- Rear access
- LCD Operator Panel (GOP or COP) – rear load only
- State of health indicators across all modules

Operating platform

- PC Core with Intel® i5 processor
- 8GB RAM 240GB / 16GB / 32GB RAM 480GB Solid State Hard Drive
- DVD-RW Drive

Software

- Microsoft Windows[®] 7 Professional / Windows[®] 10 Ready
- Supports NCR Enterprise Software platform

Additional features

- Barcode Reader 2D Barcode supports 1D/2D documents
- e-Receipts to a mobile device
- UPS (Uninterruptable Power Supply)
- NCR Interactive Banker and Teller Enterprise SW compatible
- Page turning passbook

Live Teller transactions

Extend opening hours and increase service availability with:

- Instant check cashing
- Depositing to multiple accounts in one transaction
- Card or Cardless authentication
- Bill payments
- Account to account transfers
- Customer service inquiries
- Remote Teller driven new account opening
- Loan initiation
 - Advice and assistance from a live person

*Hole in wall compatibility with NCR SelfServ 34 and Personas 84.

Weight varies by safe and can be supplied on request *Dependent on check or note quality, thickness and deposit module used. Capacity may vary by country, currency type, condition and quality of notes ****5 High Dual-dispense – requires hole in the wall

compatibility change. Height = 64.21" (1,631mm)



Why NCR?

NCR Corporation (NYSE: NCR) is a leading software and services-led enterprise provider in the financial, retail, hospitality, small business and telecom and technology industries. We run key aspects of our clients' business so they can focus on what they do best.

NCR is headquartered in Atlanta, GA with 34,000 employees and solutions in 141 countries. NCR is a trademark of NCR Corporation in the United States and other countries.

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions and operations described herein may not be marketed by NCR in all parts of the world. Consult your NCR representative or NCR office for the latest information.

All brand and product names appearing in this document are trademarks, registered trademarks or service marks of their respective holders. © 2020 NCR Corporation Patents Pending 022820-US_FM-BAN_0620 ncr.com